

Accessories

MOUNTING



The Westire NEMA Pole/Wall Mounting Bracket is ideal for surface mounting a locking type photocontrol. The Bracket can be also supplied as a kit which includes a NEMA Socket, Gasket, fastening screws and IP 67 connecting cable sealing grommet and the standard or specified length of cable. The Bracket is compatible with 3/5/7 Pin Sockets.

Configurations

844001	Pole Mounting Bracket - Receptacle not included.
844001K	Pole Mounting Bracket Kit - Includes (3 pin) Receptacle, Gasket, Screws, PG11 cable gland and 2 meters of cable
844001KXX	Pole Mounting Bracket Kit Custom Cable Length - Includes all items from 84401k, replace XX with desired cable length in meters.

RECEPTALES



The Westire NEMA receptacle is available in either 3 Pin, 5 Pin or 7 Pin configurations supplied with a sealing gasket. Receptacles meet or exceed requirements of ANSI C136.10 & C136.41 .

3 Pin Sockets utilize screw terminals, accepting upto a 4.0mm² (12 awg) conductor
5/7 Pin Sockets utilize flying leads with 30cm (12 in) length Leads

Configurations

843001	3 Pin Receptacle	With Screw terminals
843002	5 Pin Receptacle	Wiring Colors - Red, White, Black, Violet, Gray
843003	7 Pin Receptacle	Wiring Colors - Red, White, Black, Violet, Gray, Brown, Orange

CAPS



The Westire Low Profile Shorting Cap keeps the lights on or off and creates a weather proof seal to luminaire. Manufactured from the same reliable materials found in our Longlife photocell products for a dependable service life.

Available in Shorting, Open and Surge Protected Versions and Custom colors

Configurations

W6005	Shorting Cap - Black Keeps the Lights on (480 VAC Max)
W6005M	Shorting Cap - Blue Keeps the Lights on with a 320 Joule MOV (320 VAC Max)
W6007	Open Cap - Red Keeps the lights off