



Power Tap

ACCESSORIES

Ideal for providing auxiliary power to 3rd party devices



Application

The Power Tap provides auxiliary power from the NEMA socket direct to 3rd party lighting installations while continuing normal operation of the photocell e.g festival lighting, amenity lighting or security lighting

Reliability

Engineered in the EU with a 35 year design life. Manufactured in-house using only high quality name brand components, Westire products are renowned in the industry for their unparalleled quality and reliability.

Features & Benefits

- Provides mains auxiliary power for 3rd party devices such as security or festival lighting.
- Simple to install.
- Contains independent fuse for protection of auxiliary equipment.
- Rated to IP 65
- ROHS compliant
- Cable length 2 meters
- Additional cable length available on request



Technical Specifications

General		Environmental	
Dimensions	77.8 mm x 69 mm H x W	Operating Temperature	-20 C to +80 C -4 F to +176 F
Receptacle Compatibility	ANSI C136.10 / ANSI C136.41, NEMA 3 or 7 Pin	Enclosure Protection	Ultrasonically welded UV stabilised polycarbonate enclosure providing sealing up to IP65.
Warranty	5 years standard	Standards Compliance	Environmental RoHS, EN55015, EN61547, EN6100-3-2, EN6100-3-3 ETL UK 773, CSA 22.2, IS EN ISO 9001: 2015, ANSI C136.24
Cable Length	2 meters standard (other lengths available on request)		
Power			
Mains Supply	105 to 480 Volts AC - 50/60 Hz		
Power Supply Consumption	Less than 0.25 Watts		
Maximum Load Current (A)	10 Amps		
Load Rating	1800 VA Ballast / 1000 Watts		
Surge Protection	320 Joules, (840 on request)		