

Low Profile Shorting Caps

ACCESSORIES

Designed for ease of installation and minimum visual impact



Overview

Westire's Low Profile Shorting Cap is a durable, efficient method of opening or closing the Live and Load contacts of a locking type Luminaire receptacle.

Longevity

Engineered and assembled in the EU, with a 15 year design life using only name brand components and high quality materials. Westire's Shorting Caps are renowned in the industry for their unparalleled quality and reliability.

Features & Benefits

- Low profile.
- Keeps the lights on or off.
- 3 -prong Twist Lock plug connector.
- Ultrasonically sealed for exceptionally long life.
- UV stabilized polycarbonate housing is rated and tested to IP 65.
- Available in Shorting, Open and Surge Protected versions.
- Manufactured from the same reliable materials found in our Longlife photocell products for a dependable service life.

| General | | Materials | |
|----------------------|--|-----------------------------|--|
| Dimensions | 86.3mm Ø x 19.05 mm H 3.4" Ø x 0.75" H | Housing | Premium UV Stabilized Polycarbonate |
| Warranty | 5 Year Standard | Sealing Gasket | Non-shrink Neoprene Rubber Gasket |
| Standards Compliance | Environmental RoHS, EN55015, EN61547, EN6100-3-2, EN6100-3-3, IS EN ISO 9001: 2015, ANSI C136.10 | Contacts | Solid Brass Contacts |
| | | Enclosure Protection Rating | IP65 - Dust tight and protected from water spray |

Ordering Information

| Configurations | |
|----------------|--|
| W6005 | Shorting Cap. Black keeps the light on (480 VAC Max) |
| W6005 | Shorting Cap. Blue keeps the light on with a 320 joule MOV (320 VAC Max) |
| W6005 | Open-cap. Red keeps the lights off |
| | 840J version available on request |

